

SYSTEM AND METHOD FOR MEASURING  
ELECTRIC CURRENT IN A PIPELINE

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Not applicable.

STATEMENT REGARDING FEDERALLY SPONSORED  
RESEARCH OR DEVELOPMENT

[0002] Not applicable.

TECHNICAL FIELD

[0003] The present invention relates to cathodic protection systems for corrosion protection of metal objects which are buried in soil or located underwater. More particularly, the present invention relates to a system and method for measuring the electric current in a pipeline imposed by a cathodic protection system.

BACKGROUND OF THE INVENTION

[0004] The owners of pipelines frequently wish to monitor the status or condition of a pipeline or to check the integrity of a protection system. This may include measurement of the material type, internal diameter, and thickness of the pipe, the material type, and thickness of any internal lining if present, the presence of corrosion on the pipe, damage to the lining, the thickness of any deposits of material on the internal surface of the pipe or of the lining if present, the presence and extent of circumferential cracks, the presence and extent of longitudinal cracks, and the position of features such as bends, offtakes, valves and joints. In view of the high cost of replacing pipe, and the potential consequential damage due to fluid loss from a break in the pipe, it is justifiable to carry

out regular surveys of the condition of the pipe from within the pipe using a vehicle transported inside the pipe. Such vehicles are well known in the art and are often referred to as a smart or intelligent pig, hereinafter simply referred to as “pig”.

[0005] Pigs may be outfitted with electronic instruments designed to inspect pipelines internally and may physically travel with a fluid product within the pipelines without simultaneously interrupting fluid flow. As will be appreciated by those skilled in the art, a pig may detect various pipeline defects. Furthermore, due to pipelines being situated on, in, or under a diversity of terrains throughout the world, pigs are capable of traveling within multi-diameter pipelines and bends therein and are capable of detecting the location of pipe-related problems. Those skilled in the art will recognize that a wide variety of data logging devices on board pigs are well known in the art. Depending on the technology and degree of sophistication used by a pig, its sensors will record the distance traveled, location and position of features and defects, and the depth and magnitude thereof. Pigs are frequently used inside pipelines to detect the presence of corrosion and other defects.

[0006] To prevent pipe external corrosion, a cathodic protection (CP) system may be implemented. CP is a method of combating corrosion of metals that come in contact with potentially corrosive mediums. The purpose of cathodic protection is to reduce or eliminate corrosion of steel or other metals in a given environment. The corrosion of metal in an electrolyte at ambient temperature is an electrochemical process involving the flow of electrons in metals and ions in electrolytes. This corrosion can be controlled by the application of currents from an external source such as a generator or rectifier, or

from a galvanic sacrificial anode, which supplies all of the current for the electrochemical reduction of the corrodant by a source other than the corroding steel. If all of the current for the electrochemical reduction is supplied by the external source, the corrosion of the steel is reduced.

[0007] There are two widely used systems for generating opposing electrical currents, "sacrificial systems" and "impressed current systems." In sacrificial systems, the current is supplied by another metal which is galvanically more reactive than the metal of the structure. For example, metals such as aluminum, magnesium and zinc are galvanically more active than steel and are used as "sacrificial anodes" to protect steel structures. In impressed current systems, a non-consumable metal is used to drain direct current (DC) supplied from an external source into the electrolyte, which passes to the structure to be protected. The parts from which the current is drained are called "anodes" and the protected structure is called a "cathode." In both sacrificial and impressed current systems of cathodic protection, a path between the anode and the cathode is essential for flow of current to protect the structure.

[0008] In order to ensure that a CP system is properly protecting a pipeline, the prior art teaches a variety of methods for monitoring the potential difference in a pipeline imposed by the system. One such method involves installing a standard reference electrode at one or more locations along the pipeline together with a conductor connected to the pipeline. A technician periodically visits the location and measures the voltage between the standard reference electrode and the pipeline using a voltmeter. A responsible person then examines the collected data looking for inadequate voltages and variations from

earlier data and, when control is inadequate or excessive, adjusts the output(s) of the appropriate rectifier(s). Such a method is limited in that only current at static locations is measured and a technician is required to visit such locations.

**[0009]** Another commonly used potential survey method is the close interval survey in which the pipe-to-medium potential is recorded as a function of distance along the pipeline of interest. Any potentials which departed significantly from the potentials at other regions or which deviated significantly from prior surveys, could be identified as possible stray current pickup or discharge points. This method involves pipeline maintenance personnel traveling to the pipeline and making the measurements described above. Single location, time-dependent surveys are also performed by the maintenance staff by monitoring the potential at a chosen location as a function of time. Any significant changes in the recorded potentials could indicate possible intermittent pickup or discharge of stray current. This technique also provides only static data and is labor intensive

**[0010]** In yet another prior art embodiment, a downhole apparatus with a plurality of electrodes is lowered into a casing. Examples of this embodiment are given in Davies, et al., U.S. Patent No. 4,857,831, and NACE International Standard RPO186-2001 at Appendix A. The downhole apparatus is suspended by a long cable which is connected to a measurement unit located at the ground surface, and potential difference measurements are taken by the measurement unit at the ground surface as the downhole apparatus traverses the length of the casing. Since the potential difference information must be transmitted to the measurement unit at the ground surface through the long cable

connecting the downhole apparatus to the measurement unit, the information tends to be degraded due to noise pick-up and crosstalk. In addition, thermal effects along the long cable and at the electrical connections on the surface and in the downhole tool adversely affect the information. The electrodes utilized in this embodiment are not configured for dynamic electrical contact with the pipe, and, if such dynamic contact were attempted, the signal would be unacceptable due to noise distortion.

[0011] Accordingly, there is a need for improved system for monitoring electrical current imposed by a cathodic protection system over a continuum using a pig or similar vehicle for propulsion. The system should be able to dynamically and efficiently measure the voltage difference between points in a pipeline, while minimizing noise and deviations caused by thermal effects.

#### SUMMARY OF THE INVENTION

[0012] The present invention meets the above needs and overcomes one or more deficiencies in the prior art by providing a system using a propulsion vehicle that is configured to measure a voltage differential in a current-carrying pipe. The propulsion vehicle may be outfitted with two contacts for maintaining electrical contact with the pipe as the vehicle moves through the pipe. These electrical contacts may optionally include rotating steel brushes and/or rotating steel knives. The system further includes a voltage-reading device connected to the contacts for measuring the voltage between the contacts as the vehicle moves through the pipe. A vehicle according to the present invention optionally may include electromechanical devices that reduce electrical noise.

[0013] According to another aspect of the present invention, a method is provided for measuring a voltage differential in a current-carrying pipe. A propulsion vehicle having two or more contacts is inserted into a pipe. The contacts are utilized to make electrical contact with the pipe, and the voltage between the contacts is determined as the vehicle moves through the pipe. The vehicle may optionally output voltage and/or position data.

[0014] Other objects, features, and advantages of the invention will become apparent to those skilled in the art upon reference to the following detailed description of the invention and the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The present invention is described in detail below with reference to the attached drawing figures, wherein like numbers denote like parts throughout the several views:

[0016] FIG. 1 is a cut-away section of a pipe illustrating a schematic view of the present invention;

[0017] FIG. 2 is a cross section of a pipe illustrating a schematic view of another embodiment of the present invention;

[0018] FIG. 2A is a schematic view of the electrical contact 2A in FIG. 2;

[0019] FIG. 3 is a temperature compensation system according to one embodiment of the present invention; and

[0020] FIGS. 4 and 5 are exemplary test results obtained from a laboratory arrangement contemplating one embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

[0021] The present invention provides a system and method for measuring the electric current in a pipeline imposed by a cathodic protection system. To accomplish this, a pig is utilized.

[0022] Pigs are well known in the art and are frequently used inside pipelines to detect the presence of corrosion and other defects. Pigs may be outfitted with electronic instruments designed to inspect pipelines internally and may physically travel with a fluid product within the pipelines without simultaneously interrupting fluid flow.

[0023] Those skilled in the art will recognize a variety of techniques exist for tracking the location of a pipeline pig. In general, odometers have historically been used for distance/location tracking of pigs. Odometer technology has continued to improve over time with the incorporation of onboard electronic instrumentation. Other technologies have also been developed to track a pig's location in real-time using satellite (*i.e.*, GPS), subsea acoustic and other techniques for various applications. These techniques include, without limitation, Geiger counters, magnetics, radio, acoustics, pinger-based, and transponder-based systems. Those skilled in the art will recognize that any number of location tracking/logging techniques may be utilized with the present invention.

[0024] FIG. 1 shows a schematic view of a pipe **102** filled with a fluid **104**. A cut-away section 106 shows a pig **108** according to the present invention. As will be understood by those of skill in the art, the fluid **104** may propel the pig **108** through the pipe **102**. The pig **108** is in electrical contact with the internal pipeline wall **110** at electrically separated contact locations **112** and **114**. It is preferable for locations **112** and **114** to have multiple

points of contact with the wall **110**. Such electrical contact with the wall **110** is achieved by contacts **116** and **118**, which are arranged in a spaced apart relationship upon the pig **108** and which are connected to the pig body **120**. The pig body **120** further includes a voltmeter device which has leads connected to contacts **116** and **118**. Such a voltmeter is well known in the art and is capable of measuring the voltage differential between locations **112** and **114**. Pig body **120** also may include a battery, an odometer, and data-logging device, which are commercially available and well known in the art. For example, voltage and location data may be logged by the pig **108**. While the embodiment shown in FIG. 1 displays two contacts attached to a single pig, those skilled in the art will recognize that a plurality of connected pigs are acceptable use with the present invention. For example, a first pig may have a single contact, while a second pig provides the other needed contact.

[0025] An objective of the instant invention is to reduce noise resulting, in part, from the pig's movement and the invention contemplates a variety of techniques to reduce this noise. In various embodiments of the present invention, contacts **116** and **118** include rotating steel brushes and/or rotating steel knives. The brushes and knives may be utilized in various combinations to maintain electrical contact with the internal surface of the pipe **102** and, optionally, cleaning the internal surface of the pipe **102**. For example, steel brushes sold by the Weiler Corporation (Item #08047) have been used to ensure good electrical contact. A combination of three brushes and three knives for each contact may be preferable for use with the present invention to reduce noise as the contacts **116** and **118** move through the pipe **102** and rotate in the direction indicated.

**[0026]** To further reduce noise, the present invention contemplates using electromechanical devices connected to the brush and/or knife contacts **116** and **118**. In one embodiment, noise from these rotating components is reduced by using low-noise rotating electromechanical devices, such as mercury contacts and/or slip-ring contacts. Mercury contacts sold by Mercotac Inc. (Model number 110) have been used to successfully reduce noise to the microvolt range, while slip rings sold by Airflyte Electronics Company (Model #2400096-002) have been successfully used to transmit low noise signals. Those skilled in the art will recognize that any number of contact devices and/or low-noise electromechanical devices may be used with the current invention. In FIG 1, for example, pig **108** includes electromechanical devices **122** and **128**. As will be understood by those skilled in the art, device **122** includes a static element **126** and a dynamic element **124** which rotates along with the contact **116** to transmit the signal to the static element **126**.

**[0027]** FIG. 2 shows a pig **206** according to another embodiment of the present invention. The pig **206** is shown within a pipe **204**, along with the fluid **202**, which may propel the pig **206** in the direction indicated. The pig **206** is in electrical contact with the pipe **204** at electrically separated contact locations **208**, **209**, **210**, and **211**. It is only necessary, however, to implement two points of contact separated by a distance, such as points of contact **208** and **210**. Such electrical contact is achieved by the contacts being mounted in a spaced apart relationship upon the pig **206**. As discussed above, contacts **208**, **209**, **210**, and **211** may include rotating steel brushes and/or rotating steel knives. For example a combination of three brushes and three knives may be utilized with the

current invention. The contacts **208**, **209**, **210**, and **211** may further include electromechanical devices. The pig **206** further includes a battery **216**, a data logger **214**, a voltmeter **212**, and an embodiment of an odometer. These components are commercially available and well known in the art.

[0028] FIG. 2A illustrates the electrical contact **208**. As discussed above, rotating, electrical contact **208** is utilized for electrical communication with the internal pipe wall **204**. A connecting arm **254** serves to connect the contact **208** to the pig. An axel **258** runs through the arm **254** and connects the contact **208** to the pig while allowing the contact **208** to rotate in the direction indicated. The axel **258** rotates along with the contact **208** and such rotation is facilitated by ball bearing sets **260A** and **260B**. The axel **258** is in communication with an electromechanical device **262**. As will be appreciated by those skilled in the art, the electromechanical device **262** includes a dynamic element **264**, which rotates with the axel **258** and transmits the signal to a static element **266**. An electrical wire **268** emerges from the device **262**. The wire **268** may be connected to voltmeter **212**. As will be understood by those of skill in the art, to measure the voltage differential between two contacts (**208** and **210**) on a pipe, the voltmeter **212** may receive a second wire that is connected to electrical contact **210** in the manner here described.

[0029] The present invention also contemplates compensating for thermocouple voltages that result from temperature effects. FIG. 3 shows a temperature compensation system according to one embodiment of the present invention. Because of potential temperature gradients along the pipeline wall, a thermocouple voltage may be experienced, which needs to be compensated for. However, the bulk fluid temperature will be stable, and, by

measuring the thermocouple voltage difference between the pipeline wall at the electrical contact position and the bulk fluid, compensation can be made for temperature differences in the system. Different materials have to be used for the rolling contact devices with the wall in order to measure the temperature gradient for the compensation.

[0030] As shown in FIG. 3, points **302** and **304** reside upon the internal wall of a pipe. Such points may have different temperatures. The potential difference between the point **302** and the point **304** is the potential difference of interest and may be measured via a connection **306**. The reference points **308** and **310** reside within the bulk fluid **312** and are not affected by temperature deviations. Connection **314** allows the potential difference between the contact point **302** and the bulk fluid reference point **308** to be measured. Connection **316** allows the potential difference between the contact point **304** and bulk fluid reference point **310** to be measured. Because of potential temperature differences at the pipe wall, thermocouple effects induce some of the voltage measured at the contacts. By measuring the voltage differences between the contacts and the references, these effects can be compensated for and the true potential difference between points **302** and **304** can be calculated.

[0031] The accuracy of the pig's data may also be adversely affected by no-contact events. No-contact events refer to an event in which the electrical contact between the pig and pipeline is interrupted. Those skilled in the art will recognize that no-contact events result in undesirable open-circuit signals. To detect no-contact events, the present invention may include an alternating current (AC) pilot signal to flag and exclude no-contact signals during data processing. For example, if a 1-10 kHz AC voltage source of

1mV is incorporated into the electrical circuitry, a band-pass filter at the frequency of the source filters the pilot signal out. When the signal is present, there must be contact, while no signal indicates no contact. The use of an AC pilot signal is provided as an example, and those skilled in the art will recognize that a variety of techniques may be acceptable to flag no contact events.

[0032] A variety of laboratory tests have demonstrated the performance of the present invention, and FIGS. 4 and 5 display exemplary test results. An artificial on-off voltage of 40 microvolt was incorporated into the electric circuit to see whether the intermittent voltage could be retrieved. The signal was successfully retrieved in each test. In FIG. 4, the speed of the rolling, rotating contacts was approximately 1.1 meters per second. Graph 400 displays exemplary results of this test. As shown in the graph 400, moderate baseline drift was experienced by the output. Thermo-effects, for which no compensation was made, caused this drift. FIG. 5 displays results of the same test, except that the speed of the rolling, rotating contacts was approximately 2 meters per second, which is on the high side of typical velocities seen in transportation of liquids. Graph 500 displays exemplary results of this test. Slightly greater base line drift was experienced because the increased speed of the contacts produced greater thermal dynamic effects, for which no compensation was attempted.

[0033] As a result of these and additional tests, it has been shown that a pig according to the present invention can successfully measure the electric current in a pipeline imposed by a cathodic protection system. High-quality, rotating electrical contacts are preferred for transmitting low-voltage signals, while both rolling brushes and knives are suitable for

making electrical contact with the pipe wall. Furthermore, temperature compensation is required for elimination of thermocouple signals.

**[0034]** The subject matter of the present invention is described with specificity to meet statutory requirements. However, the description itself is not intended to limit the scope of this patent. Rather, the inventors have contemplated that the claimed subject matter might also be embodied in other ways, to include different steps or combinations of steps similar to the ones described in this document, in conjunction with other present or future technologies. Moreover, although the term “step” may be used herein to connote different elements of methods employed, the term should not be interpreted as implying any particular order among or between various steps herein disclosed unless and except when the order of individual steps is explicitly described. Alternative embodiments and implementations of the present invention will become apparent to those skilled in the art to which it pertains upon review of the specification, including the drawing figures.